ABA CHAPTER 2: SCOPING REQUIREMENTS

ARCHITECTURAL BARRIERS ACT: SCOPING

two or more composite play structures designed for the same age group, the total number of elevated play components on all the composite play structures must be added to determine the additional number and types of ground level play components that must be provided on an accessible route.

Advisory F240.2.1.2 Additional Number and Types. Where a large play area includes

F240.2.2 Elevated Play Components. Where elevated play components are provided, at least 50 percent shall be on an accessible route and shall comply with 1008.4. Advisory F240.2.2 Elevated Play Components. A double or triple slide that is part of a

composite play structure is one elevated play component. For purposes of this section, ramps, transfer systems, steps, decks, and roofs are not considered elevated play components. Although socialization and pretend play can occur on these elements, they are not primarily intended for play. Some play components that are attached to a composite play structure can be approached or exited at the ground level or above grade from a platform or deck. For example, a climber attached to a composite play structure can be approached or exited at the ground level or above grade from a platform or deck on a composite play structure. Play components that are attached to a composite play structure and can be approached from a platform or deck

(e.g., climbers and overhead play components) are considered elevated play components. These play components are not considered ground level play components and do not count toward the requirements in F240.2.1.2 regarding the number of ground level play

components that must be located on an accessible route.

F241.1 General. Where provided, saunas and steam rooms shall comply with 612. EXCEPTION: Where saunas or steam rooms are clustered at a single location, no more than 5

F241 Saunas and Steam Rooms

required to comply with 612.

F242 Swimming Pools, Wading Pools, and Spas

F242.1 General. Swimming pools, wading pools, and spas shall comply with F242.

F242.2 Swimming Pools. At least two accessible means of entry shall be provided for swimming pools. Accessible means of entry shall be swimming pool lifts complying with 1009.2; sloped entries complying

percent of the saunas and steam rooms, but no fewer than one, of each type in each cluster shall be

with 1009.3; transfer walls complying with 1009.4; transfer systems complying with 1009.5; and pool

stairs complying with 1009.6. At least one accessible means of entry provided shall comply with 1009.2

or 1009.3.

EXCEPTIONS: 1. Where a swimming pool has less than 300 linear feet (91 m) of swimming pool

wall, no more than one accessible means of entry shall be required provided that the accessible means of entry is a swimming pool lift complying with 1009.2 or sloped entry complying with 1009.3.

to one area shall not be required to provide more than one accessible means of entry provided that 139

2. Wave action pools, leisure rivers, sand bottom pools, and other pools where user access is limited